

# PARTS & SERVICE NEWS

REF NO.	AA03172
DATE	December 05, 2003

**SUBJECT:** NEW, IMPROVED OPERATOR ARM/WRIST REST

**PURPOSE:** To introduce a new, larger wrist rest for added comfort.

**APPLICATION:** Komatsu Wheel Loaders:  
 WA500-3: 50001 & Up;  
 WA500-3L: A70001 - A70832;  
 WA500-3LK: A71001 - A71224, A72001 & Up;  
 WA600-3: 52001 & Up;  
 WA600-3L: A52001 - A52224;  
 WA600-3LK: A53001 - A53051;  
 WA700-3: 50001 & Up;  
 WA700-3L: A50001 & Up;  
 WA800-3: 50001 & Up;  
 WA800-3LC: A50001 - A50029;  
 WA900-3: 50001 & Up;  
 WA900-3LC: A50001 - A50035

**FAILURE CODE:** 54JSZ9

**DESCRIPTION:** Arm/Wrist Rest Improvement Kit (LK4037)

A larger sized wrist rest is now available to provide increased operator comfort. In addition to the larger size, the cover material has been changed to a more durable woven fabric. Refer to Figures 1 & 2 for the difference in size. Refer to Table 1 for complete listing of the kit contents.



FIGURE 1. PREVIOUS WRIST REST

- 1. Pad
- 2. Mounting Bracket
- 3. Adjustment Lever



FIGURE 2. NEW ARM/WRIST REST

- 1. Pad
- 2. Mounting Bracket

<b>Part Number</b>	<b>Description</b>	<b>Quantity</b>
427-54-A2620	Pad	1
427-54-A2610	Bracket	1
01435-00825	Bolt	2

### **Removal And Installation**

1. Rotate adjustment lever (3, Figure 1) backward toward the rear of the cab in order to release the mounting bracket.
2. Lift the bracket and pad assembly from the console.
3. Place the new pad into position on the new bracket.
4. Install the two bolts that secure the pad and tighten to  $3.2 \pm 0.3$  kgm ( $31 \pm 3$  Nm).
5. Place the assembly into position in the console.
6. Rotate the adjustment lever forward toward the front of the cab to lock the bracket at the desired height.

<https://hespareparts.com/>