PARTS & SERVICE

Ref. No.	AH98025			
Date	07.10.1998			
	Page	1	of	1

Subject:

Connector for multi-purpose bucket and hose protector

Purpose: hose

Modification of connector for multi-purpose bucket and additional

protector


Application:

WA75-3 / WA85-3

Description:

In the further of technical development the left quick attach coupler from the additional control circuit and the long hydraulic hose from the multi-purpose bucket was been modified.

If required we recommend this additional modification




Modification of the guick attach coupler:

- Set the change over lever into its position "2"

- Rebolt the quick-change unit remove the hydrauic hose from the quick attach coupler.

- Remove the hydraulic pipe (1) from the block.
- Remove the bracket with (2) with bick and coupler from the boom.
- Remove the bracket (2) from the black.
- Screw on the new bracket (Pos. Von the block.
- Remove the circlip (3).
- Remove the quick attach counter (4).
- Set on the spring (4) put the straight end of spring into the 4 mmhole of the new bracket.
- Set on the cuick attach coupler (4).
- Mount the circlip (ട).
- Screw or the bracket with block and coupler on the boom and tighten
- Screwor the hydraulic pipe (1) at the block.



Modification of multi-purpose bucket:

- Set the hose protector (Pos.3) onto the hose

Spare parts:

Pos.	Name	P/N	Qty
1	Bracket	42U-70-12J60	1
2	Spring	42U-70-12K10	1
3	Hose protector	42U-09-H1980	1

KOMATSU